



Respiratory Therapy

# iCH PLUS

Continuous Positive Airway Pressure

The iCH CPAP system is designed to fit nicely into your life and home, providing comfortable therapy with an attractive design; it is a perfect fit to support you in meeting your prescribed treatment goals.

A built-in heated humidifier maximizes comfort, and ultra-quiet operations allow you to sleep peacefully throughout the night. For people on the move, this product is built for travel; it is compact, lightweight and easy-to-pack. The iCH is a CPAP that doesn't look like a CPAP; its sleek design allows you to place it anywhere in your home.





## Features:

## Stylish Design

- Fashionable consumer-oriented design
- Sleek, high quality and robust exterior case
- Cool blue lighting in water chamber

## Compact &amp; Portable

- Small footprint requires less space at the bedside
- Lightweight structure
- DC input (for use in vehicles)

## User Friendly and Convenient

- SD card and mini USB connector for therapy data extract
- Anti back-flow baffle (prevents spillage from water chamber)
- Recessed, hidden handle for easy pick-up and carry

## The iCH Series: Features Overview

Model	iCH PLUS	iCH AUTO
Ramp Starting Pressure	⊙	⊙
Auto-Adjusting Pressure		⊙
Auto Altitude Adjustment	⊙	⊙
Leak Compensation	⊙	⊙
Low Pressure Auto-off	⊙	⊙
Efficiency Reporting (AHI, Leak)	⊙	⊙
Compliance Reporting	⊙	⊙
Playback Software	⊙	⊙
Dual Downloading Ports (Memory Card & Cable)	⊙	⊙
Clock/Alarm Function	⊙	⊙
PVA Function	⊙	⊙



## Specifications:

Pressure Range (cmH2O):	4.0 - 20.0 (0.5 cmH2O increment)
Ramp Time (min):	0-45 (5 min increment)
Ramp Starting Pressure (cmH2O):	3.0 to Therapy pressure (0.5 cmH2O increment)
Data Storage:	300 summary sessions 18 detailed session
Sound Level:	under 28 dBA*
Humidification:	Patient-adjustable; 6 settings
Water Capacity:	300 ml
Dimensions (W x D x H):	6.5" x 7.8" x 6.9" (16.5 cm x 19.7 cm x 17.4 cm)
Weight:	1.14kg ( .51 lbs)
Power Supply:	AC: 100V-240V, 50/60Hz, universal power supply DC: 24V
Operating Range:	+5°C to +35°C (+41°F to +95°F); 15% to 95%RH non-condensing
Storage Range:	-15°C to +50°C (+5°F to +122°F); 10% to 90%RH non-condensing
EN60601-1 Classification:	Class II, Type BF, IPX0, IEC 60601-1-2 EMC Compatibility

Specifications are subject to change for improvement without notice.

**APEX MEDICAL CORP.**

9, Min Sheng St. Tu-Cheng,  
Taipei County, 236, Taiwan, R.O.C.  
TEL: 886-2-22683100  
FAX: 886-2-22686525  
E-mail:marketing@apexmedical.com.tw  
www.apexbrand.com

**APEX MEDICAL S.L.**

Máximo Aguirre 18 Bis, 8ª planta  
48011 Bilbao (Vizcaya)  
Tel: (+34) 94.470.64.08  
Fax: (+34) 94.470.64.09  
E-mail: info@apexmedical.es  
www.apexbrand.com