


JOYCE SilkGel

Silky soft wearing comfort: the new SilkGel masks in the JOYCE family

JOYCE SilkGel is the new gel variant of the proven masks in the JOYCE family. It is available as a nasal or a full face mask. The newest generation of our customizable masks is distinguished by its high degree of wearing comfort. The mask seal and the forehead cushion have been given a high-quality coating called WEINMANN SilkTec. The smooth surface is soft and silky for guaranteed comfort. The new gel forehead cushion and the headgear with optimized design add the perfect finishing touches to the SilkGel masks.



JOYCE SilkGel Full Face, WM 26428

JOYCE SilkGel, WM 26128

Operating Ease and Wearing Comfort

- Even greater wearing comfort, thanks to the new high-quality coating WEINMANN SilkTec: It ensures a silky soft feeling on the face and reduces shear force.
- Extremely easy to clean because hardly anything (perspiration and the like) adheres to the smooth surface
- For easy assembly the forehead cushion is fitted into pockets that hold it in place.
- Easy to manage headgear: The optimized design and the color-coded Velcro fasteners make the headgear even easier to handle.
- Tube anchoring strap on the headgear as optional fastening option for device tube
- Is delivered in a carton
- Additional storage and transport bag
- Single-layer mask seal makes mask particularly hygienic
- Simple to adjust, perfect fit













- Only gel mask with ball-and-socket joint
- Mask seal and forehead cushion of gel
- Many replacement parts available
- Available in sizes S, M and L

Therapy Convenience

- All-around movable ball-and-socket joint for freedom of movement and a sure and stable mask fit
- The very quiet exhalation system promotes restful sleep for patient and sleeping partner.
- Unique modular design ensures a perfect fit as nearly all silicone and gel components can be combined with each other.
- Pressure range of 4 to 40 mbar
- The quick-release cord, which allows fast detachment of the mask, is optionally available for all JOYCE SilkGel full face masks.

Product Description	Article no. Size S	Article no. Size M	Article no. Size L
JOYCE SilkGel vented	26118	26128	26138
JOYCE SilkGel non-vented	26168	26178	26188
JOYCE SilkGel Full Face vented	26418	26428	26438
JOYCE SilkGel Full Face non-vented	26468	26478	26488

Replacement Parts

For both masks		Nasal Mask	Full Face Mask
Headgear incl. headgear clips WM 26350 	Cap for pressure measurement ports WM 26208 	Mask cushion SilkGel, S WM 26152 	Mask cushion SilkGel, S WM 26452 
	Rotating sleeve WM 26288 	SilkGel, M WM 26153 	SilkGel, M WM 26453 
	Ball-and-socket Set NV (blue) Retaining ring NV, elbow NV and rotating sleeve NV WM 26207 	Ball-and-socket joint Set, vented Retaining ring, elbow, rotating sleeve WM 15672 	Ball-and-socket joint Set, Full Face vented Retaining ring, elbow, rotating sleeve and anti-asphyxia valve WM 15674 
Tube anchoring strap WM 26774 			
Headgear clips 4 pieces WM 26205 			
SilkGel forehead cushion WM 26270 			
SilkGel forehead support incl. SilkGel forehead cushion, coarse and fine adjustment components WM 15673 	Carrying bag (not shown) WM 26295	Outer Packaging nasal (not shown) WM 14611	Outer Packaging Full Face (not shown) WM 14612

You'll find our complete range of therapy solutions, accessories and mask systems at: weinmann.de.

Accessories

Quick-release
 Quick-release cord (ripcord)
 WM 26560

Technical Data JOYCE SilkGel



	Nasal Mask	Full Face-Mask		Nasal Mask	Full Face-Mask
Product Class as per 93/42/EWG:	II a		Flow Resistance		
Dimensions (W x H x D):	about 80 x 130 x 90 mm ¹	about 107 x 160 x 106 mm ¹		■ Vented variants at 50 l/m: 0.02 hPa at 100 l/m: 0.26 hPa	0.02 hPa 0.11 hPa
Weight:	about 85 g ¹	about 102 g ¹		■ Non-vented variants at 50 l/m: 0.09 hPa at 100 l/m: 0.37 hPa	0.09 hPa 0.37 hPa
Therapy pressure range:	4 hPa to 40 hPa			■ Anti-asphyxia valve at 50 l/m: – at 100 l/m: –	0.5 hPa 2.0 hPa
Tube connection conus as per EN ISO 5356-1:			Declared duad noise emission values in compliance with ISO 4871, uncertainty factor 3 dB(A)		
■ vented variants: Ø 22 mm (male) ■ non-vented variants: Ø 22 mm (female)			■ Sound intensity level: 15 dB(A) ■ Sound power level: 23 dB(A)	16.5 dB(A) 24.5 dB(A)	
Pressure measurement connection:	Ø 4 mm		Hydraulic Pressure Anti-asphyxia valve (vented variants)		
Temperature Range			■ open: – ■ closed: –	≤ 1 hPa ≤ 2 hPa	
■ Operation: +5 °C to +40 °C ■ Storage: -20 °C to +70 °C					
Service Life:	up to 12 Monate ²				

¹ Depends on size and variant

² Materials used in the manufacture of the mask age faster when they are subjected to strong cleaning agents. Therefore, in isolated cases it may be necessary to replace the mask earlier.